

Three-Phase-Asynchronous-Motor AOA 132 SA 2/PHE

IE3OG13SA202



General data

Type of motor	3~
Type designation	AOA
Frame size	132
Mounting	B3
Frame execution	S
Frame material	Aluminium
Insulation class	F/B
Terminal box location	top DE
Terminal box orientation	cable gland to the right side
Weight (kg)	43,00
Rotation Direction	right /left
Vibration level	A
Balancing method	half key
cooling type	IC411
Executed acc. to noise level	IEC 60034-1 IEC 60034-9

Electrical data

Power 1 50Hz (kW)	5,50
Power 1 60Hz (kW)	5,50
Frequency (Hz)	50/60
Voltage 50Hz (V)	400/690
Voltage 60Hz (V)	460/-
Voltage/Frequency tolerance (not valid for range voltage)	range B
Connection	Δ/Y
Poles	2
Efficiency 100% 50Hz (%)	89,2
Efficiency 75% 50Hz (%)	90,5
Efficiency 50% 50Hz (%)	90,6
Efficiency 100% 60Hz (%)	89,5
Efficiency 75% 60Hz (%)	90,4
Efficiency 50% 60Hz (%)	89,8
Power factor	0,84
Starting current (Ia/In)	7,6
Starting torque (Ma/Mn)	2,8
Breakdown torque (Mk/Mn)	3,6
Current 50Hz (A)	10,60/6,15
Current 60Hz (A)	9,18
Eff.Cl.50Hz	IE3
Eff.Cl.60Hz	IE3

Motor characteristics

Color	RAL7030
Paint surface	shiny
Paint coating	C3
Protection class	IP55
Cable gland size (cable connection)	2xM32x1,5
Cable gland size (option)	M16x1,5
Cable gland type	Standard
Shaft end (mm)	38 x 80
Shaft material	C45
Specification NDE	Plastic fan

Mechanical data

Torque (Nm)	18,02/15,03
Rotation speed (1/min)	2915/3495
Bearing DE	6208.ZZ.C3
Bearing NDE	6208.ZZ.C3
Mounting of bearing DE	loose bearing
Mounting of bearing NDE	loose bearing
Bearing lifetime (h)	20000
allow. Radial load (X0) (N)	1610
allow. Radial load (Xmax) (N)	1275
Moment of inertia (kgm ²)	0,0146

Influencing factors

Duty	S1
Ambient temperature (°C)	-20 up to +40
Height of location (m)	1000

Additional options

Protection winding	PTC 150°C
Condensate draining hole	✓
Condensate draining hole sealing screw	✓

Technical changes and errors reserved.

AC Motoren GmbH
Einsteinstr. 17
D-64859 Eppertshausen

+49 6071 49 887 -0
team@ac-motoren.de
www.ac-motoren.com

Sparkasse Dieburg
IBAN: DE87 5085 2651 0148 0115 21
BIC: HELADEF1DIE


Postbank Frankfurt
IBAN: DE80 5001 0060 0750 8446 04
BIC: PBNKDEFF

21.07.2025

Drawings

Three-Phase-Asynchronous-Motor AOA 132 SA 2/PHE IE3OG13SA202

Die Zeichnung dient lediglich als Skizze um Maße darzustellen. Das gelieferte Produkt kann von dieser Skizze abweichen. Die detaillierte Beschreibung des Produkts befindet sich im Datenabschnitt (Seite 1).
The drawing serves only as a sketch to show dimensions. The delivered product may differ from this sketch. The detailed description of the product can be found in the Data section (page 1).



LB	IPE/KK	DH	K	G	LL	LD	L	AG	GD	F	HA	H	E	D	C	BB	B	AD	AC	AB	AA	A
349	M32x1,5	M12	18	33,00	139,00	202,00	429,00	137,00	8	10	15	132	80	38	89	175	140	180	264	274	50	216